




TECHNICAL DETAILS

Type	Model	Power kW		Electric power supply	Fan motor kW	Pump motor kW	Gas connections	Noise level dBA
		min.	max.					
C83X	MG.xx.xP.xx.0.xx	200	830	230/400 V 3N ac	1,1	0,55	1"¼ - 1"½ - 2" - DN65	< 80

For the configuration of the gas train, see page 101.



Type	Packaging dimensions (mm)			
	l	p	h	kg
C83X	1730	1280	1020	140

Approximate values

Type	Model	Overall dimensions (mm)																																
		AA	AC	AD	AE	AS	AL	BB	BS	BL	C	CC	D	E	F	G	H	I	J	K	L	M	N	O		P	Q	R	S	U	V	W	Y	Z
																								min.	max.									
C83X	MG.xx.xP.xx.A.0.32	87	224	28	306	1134	1284	328	300	450	834	342	1008	634	374	240	270	198	241	300	335	M10	330	216	250	233	387	131	256	541	-	490	162	155
C83X	MG.xx.xP.xx.A.0.40	87	224	28	306	1134	1284	328	300	450	834	342	1008	634	374	240	270	198	241	300	335	M10	330	216	250	233	458	131	327	541	-	490	162	155
C83X	MG.xx.xP.xx.A.0.50	87	224	28	306	1134	1284	328	300	450	834	342	1008	634	374	240	270	198	241	300	335	M10	330	216	250	233	471	131	340	525	-	490	162	155
C83X	MG.xx.xP.xx.A.0.65	87	224	28	306	1134	1284	328	300	450	834	342	1094	720	374	240	270	198	241	300	335	M10	330	216	250	233	571	131	440	593	292	490	162	155

Approximate values