


TECHNICAL DETAILS

Type	Model	Power kW		Electric power supply	Fan motor kW
		min.	max.		
L0140	G-.TN.x.xx.A	80	160	230 V 1N ac	0,18
L0140	G-.AB.x.xx.A	38	160	230 V 1N ac	0,18
LOX140	G-.TN.x.xx.A	64	130	230 V 1N ac	0,18
L0200	G-.TN.x.xx.A	80	200	230 V 1N ac	0,18
L0200	G-.AB.x.xx.A	38	200	230 V 1N ac	0,18



Type	Packaging dimensions (mm)			
	l	p	h	kg
L0140..S	600	370	400	25
L0140..L	750	370	400	25
LOX140..S	600	370	400	25
LOX140..L	750	370	400	25
L0200..S	600	370	400	25
L0200..L	750	370	400	25

Approximate values

Type	Model	Overall dimensions (mm)											Boiler drilling (mm)				Burner flange (mm)		
		A	B		C		D	G	Y	L	T	X	H	M	N	P	K	O	
			min.	max.	min.	max.												min.	max.
L0140	G-.xx.S.xx.A	560	80	170	390	475	373	108	108	244	32	338	128	M8	188	133	188	108	158
L0140	G-.xx.L.xx.A	660	80	270	390	575	373	108	108	244	32	338	128	M8	188	133	188	108	158
LOX140	G-.xx.S.xx.A	560	80	170	390	475	373	108	108	244	32	338	128	M8	188	133	188	108	158
LOX140	G-.xx.L.xx.A	660	80	270	390	575	373	108	108	244	32	338	128	M8	188	133	188	108	158
L0200	G-.xx.S.xx.A	560	65	170	390	475	373	108	108	244	32	338	128	M8	188	133	188	108	158
L0200	G-.xx.L.xx.A	660	65	270	390	575	373	108	108	244	32	338	128	M8	188	133	188	108	158

Approximate values

MECHANICAL OPERATION

L0140					L0200				
Model	Operation	Code	Price €		Code	Price €			
G-.TN.S.xx.A	TN	026050101			026050301				
G-.AB.S.xx.A	AB	026050102			026050302				

LOX140				
Model	Operation	Code	Price €	
G-.TN.S.xx.A	TN	026050901		

S = Standard combustion head (BS)

L = For long combustion head version (BL) increase the price (see price list)

In compliance with:

- Low Tension Directive 2014/35/UE - Electromagnetic Compatibility Directive 2014/30/UE - Machinery Directive 2006/42/CE