


PNEUMATIC ATOMIZATION WITH ELECTRONIC OPERATION
with viscosity up to 4000 cSt at 50°C (530°E at 50°C)

TECHNICAL DETAILS

Type	Model	Output kW		Auxiliary electrical power supply	Motor electrical power supply	Fan motor	Pump motor	Resistor	Gas connections
		min.	max.			kW	kW	kW	Rp
KPBY91	MH.xx.S.xx.A.1.xxx.xx	480	2.670	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	4,0	0,75	8,0	2" - DN65 - DN80 - DN100
KPBY92	MH.xx.S.xx.A.1.xxx.xx	480	3.050	230 V 1N AC 50 Hz	400 V 3 AC 50 Hz	5,5	0,75	12,0	2" - DN65 - DN80 - DN100

For the configuration of the gas train, see page 112-113.



Low pressure pump set (pump, motor and filter) is included, but supplied loose (not assembled on the burner).

Type	Model	Overall dimensions (mm)																														
		DN	A	AA	AN	B*	BB	C	CC	D	DD	E	F	G	H	J	K	L	M	O		P	R	S	U	V	W	Z	T	Y	PP	QQ
		min.		max																												
KPBY91	MH.xx.x.xx.1.50	50	1475	240	600	490	419	985	532	1372	510	852	520	365	405	456	360	550	M12	280	310	500	166	374	624	-	798	185	43	228	500	550
KPBY91	MH.xx.x.xx.1.65	65	1475	240	600	490	419	985	532	1569	510	1049	520	365	405	456	360	550	M12	280	310	500	166	483	843	292	798	185	43	228	500	550
KPBY91	MH.xx.x.xx.1.80	80	1475	240	600	490	419	985	532	1604	510	1084	520	365	405	456	360	550	M12	280	310	500	166	535	875	322	798	185	43	228	500	550
KPBY91	MH.xx.x.xx.1.100	100	1475	240	600	490	419	985	532	1687	510	1167	520	365	405	456	360	550	M12	280	310	500	166	642	942	382	798	185	43	228	500	550
KPBY92	MH.xx.x.xx.1.50	50	1475	240	600	490	419	985	532	1372	510	852	520	365	405	456	360	550	M12	280	310	500	166	374	624	-	798	185	43	228	500	550
KPBY92	MH.xx.x.xx.1.65	65	1475	240	600	490	419	985	532	1569	510	1049	520	365	405	456	360	550	M12	280	310	500	166	483	843	292	798	185	43	228	500	550
KPBY92	MH.xx.x.xx.1.80	80	1475	240	600	490	419	985	532	1604	510	1084	520	365	405	456	360	550	M12	280	310	500	166	535	875	322	798	185	43	228	500	550
KPBY92	MH.xx.x.xx.1.100	100	1475	240	600	490	419	985	532	1687	510	1167	520	365	405	456	360	550	M12	280	310	500	166	642	942	382	798	185	43	228	500	550

Approximate values

* The dimension B is reduced by 20 mm with counterflange and gasket.